

FOUR HILLS IMPROVEMENTS



INSTALL NEW "NO PARKING PRIVATE DRIVE" SIGN (12"x18") AT THE START OF PRIVATE DRIVEWAY

INSTALL SIGN OM3-R (8"x24") INTO PREFORMED HOLE IN FRONT CENTER OF THE MEDIAN



INSTALL 3 YELLOW RPMs ON TOP OF MEDIAN CURB

INSTALL 24" WHITE THERMOPLASTIC STOP BAR

R 1' FT

R 4' FT

R 8' FT

EXTEND WHITE THERMOPLASTIC STRIPE TO NEW CURB RETURN

R 8' FT

R 4' FT

R 1' FT

EXTEND WHITE THERMOPLASTIC STRIPE TO NEW CURB RETURN

INSTALL 3 YELLOW RPMs ON TOP OF MEDIAN CURB

INSTALL SIGN OM3-R (8"x24") INTO PREFORMED HOLE IN FRONT CENTER OF THE MEDIAN



CONSTRUCTION NOTES

- ① PAVE MEDIAN USING DECORATIVE MEDIAN PAVING, COLOR: SAN DIEGO BUFF, PATTERN: ASHLAR SLATE.
- ② CONSTRUCT HEADER CURB ADJACENT TO EXISTING LIP OF GUTTER PER COA STD DWG.
- ③ CONSTRUCT MEDIAN CURB AND GUTTER ALONG THE OUTSIDE PERIMETER OF THE NEW BULB OUT.
- ④ REMOVE AND REPLACE GUTTER TO NEAREST JOINT.
- ⑤ PAINT OUTSIDE OF PERIMETER OF NEW MEDIAN CURB YELLOW.
- ⑥ REMOVE AND REPLACE YELLOW THERMOPLASTIC STRIPE TO MEET NEW 10' FOOT LANE WIDTH.

10' LANE

10' LANE

33'

30'

